

The image features a central white rectangular area with a chain-link fence pattern. This area is framed by a solid orange border at the top and bottom. The background outside the white area is black. The text is centered within the white area.

BEST ONNO

Iron and Steel Company

BEST ONNO

Iron and Steel Company

ABOUT US

- ✓ Company that distributes wire and fences and it has presence in 4 continents and 14 countries.
- ✓ Constant growth year by year, providing seriousness and reliability to our client and giving them excellent service and attention.



BEST ONNO
Iron and Steel Company

KEY DATES OF OUR WIRE & SERVICE



ASSURED QUALITY



COMPETITIVE PRICE



RELIABLE DELIVERY DATES



PERSONAL AND DECISIVE ATTENTION



BEST ONNO
Iron and Steel Company

STANDARDS OF OUR WIRE

- ✓ ASSURED QUALITY (*STANDARD: EN 10016-2*)
- ✓ DIAMETER TOLERANCE (*STANDARD: UNE-EN 102 18-2 (MM.)*)
- ✓ ZINC COATED (*STANDARD: UNE-EN 10244-2 (GR/M2)*)
- ✓ TENSILE STRENGTH
 - HARD: 60 – 107 KG/MM²
(*depend on diameter*)
 - SOFT: 45 – 55 KG/MM²

	Diameter (mm)	Diameter Tolerance	Tensile strength (kg/mm ²)		Zinc Coated (gr/m ²)
			Recocido	Duro	
COMMERCIAL GALVANIZED	1.60	+/-0.04	45 - 55	80 - 107	>25
	1.80	+/-0.04		85 - 100	>30
	2.00	+/-0.04		80 - 100	>40
	2.20	+/-0.04		75 - 100	>45
	2.40	+/-0.05		75 - 95	>45
	2.70	+/-0.05		75 - 90	>45
	3.00	+/-0.05		75 - 85	>50
	3.40	+/-0.05		70 - 85	>60
	3.90	+/-0.06		68 - 80	>60
	4.40	+/-0.06		65 - 80	>70
	4.90	+/-0.06		62 - 80	>70
5.40	+/-0.06	62 - 70	>80		
HEAVY GALVANIZED	1.60	+/-0.05	45 - 55	85 - 95	>195
	1.80	+/-0.05		80 - 95	>205
	2.00	+/-0.05		80 - 95	>215
	2.20	+/-0.06		75 - 95	>230
	2.40	+/-0.06		70 - 95	>230
	2.70	+/-0.06		70 - 90	>245
	3.00	+/-0.07		70 - 85	>255
	3.40	+/-0.07		65 - 85	>265
	3.90	+/-0.07		65 - 80	>275
	4.40	+/-0.08		65 - 75	>275
	4.90	+/-0.09		60 - 75	>275

	Diameter (mm)	Diameter Tolerance	Tensile strength (kg/mm ²)		Zinc Coated (gr/m ²)
			Recocido	Duro	
COMMERCIAL GALVANIZED	1.60	+/-0.04	45 - 55	80 - 107	>25
	1.80	+/-0.04		85 - 100	>30
	2.00	+/-0.04		80 - 100	>40
	2.20	+/-0.04		75 - 100	>45
	2.40	+/-0.05		75 - 95	>45
	2.70	+/-0.05		75 - 90	>45
	3.00	+/-0.05		75 - 85	>50
	3.40	+/-0.05		70 - 85	>60
	3.90	+/-0.06		68 - 80	>60
	4.40	+/-0.06		65 - 80	>70
	4.90	+/-0.06		62 - 80	>70
	5.40	+/-0.06	62 - 70	>80	
HEAVY GALVANIZED	1.60	+/-0.05	45 - 55	85 - 95	>195
	1.80	+/-0.05		80 - 95	>205
	2.00	+/-0.05		80 - 95	>215
	2.20	+/-0.06		75 - 95	>230
	2.40	+/-0.06		70 - 95	>230
	2.70	+/-0.06		70 - 90	>245
	3.00	+/-0.07		70 - 85	>255
	3.40	+/-0.07		65 - 85	>265
	3.90	+/-0.07		65 - 80	>275
	4.40	+/-0.08		65 - 75	>275
	4.90	+/-0.09		60 - 75	>275